



# RECESSED ESCUTCHEONS AND COVER PLATES TO MEET IBC-ASCE/SEI 7 CODES FOR SEISMIC AREAS C, D, & E

## RECESSED ESCUTCHEONS

### 2 PIECE RECESSED

1/2" Adjustable

**Finish/Part No. 1/2"NPT**

**Finish/Part No. 3/4"NPT**

- Chrome: 326201
- White: 326203-W

- Chrome: 326208
- White: 326210-W

### 1/2" Adjustable Recessed Model Numbers

**cULus Listed:** GL2810, GL4110, GL4210, GL4230, GL4231, GL4234, GL4710, GL5628, GL5630, GL5631, GL8101, GL8107, GL8128, GL8129, GL8151 & GL8174

**cULus Listed & FM Approved:** GL5601, GL5635, GL8106 & GL8156

FOR FULL DESCRIPTIONS SEE SPECIFIC DATA PAGES

3/4" Adjustable

**Finish/Part No. 1/2"NPT**

**Finish/Part No. 3/4"NPT**

- Chrome: 326170
- White: 326172-W

- Chrome: 326177
- White: 326179-W

### 3/4" Adjustable Recessed Model Numbers

**cULus Listed:** GL2801, GL2826, GL2851, GL2870, GL4201, GL4226, GL4231, GL4251, GL4270, GL501, GL5602, GL5626, GL5628, GL5635, GL5636, GL5641, GL5642, GL5652, GL5670, GL5680, GL5685, GL5686, GL8101, GL8102, GL8106, GL8107, GL8109, GL8127, GL8128, GL8129, GL8135, GL8141, GL8152, GL8157, GL8159, 8171, GL8174, GL8179 & GL8185

**cULus Listed & FM Approved:** GL5651, GL5679, GL8151 & GL8156

FOR FULL DESCRIPTIONS SEE SPECIFIC DATA PAGES

## CONCEALED COVER PLATES

FOR "THE INCH" Quick Response **GL5606** & Standard Response **GL5653**

**Finish/Part No. 135°F**

**Finish/Part No. 155°F**

- Chrome: 332821
- White: 332822

- Chrome: 332827
- White: 332828

**cULus Listed:** GL5606 & GL5653

FOR FULL DESCRIPTIONS SEE SPECIFIC DATA PAGES



OPTIONAL IBC SEISMIC **WHITE** RECESSED ESCUTCHEON



OPTIONAL 4 1/2" DIAMETER **WHITE** ADJUSTABLE CONCEALED COVER PLATE

# CONCEALED SPRINKLER COVER PLATES

## COMMERCIAL CONCEALED COVER PLATES

### Flat Plate “3-Step” Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 325435
- White: 325437

#### Finish/Part No. 155°F (68°C)

- Chrome: 325440
- White: 325442



- cULus Approved:** *GL2804, GL2854, GL4204, GL4254, GL5604, GL5605, GL5637, GL5638, GL5654, GL5681, GL5682, GL8137, GL8181* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate; *GL5655* - 135° (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate
- FM Approved:** *GL5654* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate; *GL5637, GL5681* - 135° (57°C) Sprinkler with 155°F (68°C) plate; 155°F (68°C) Sprinkler with 200°F (93°C) plate
- LPC, CE Approved:** *GL5604, GL5654* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155° (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- FOR FULL DESCRIPTION SEE PAGES: A-32, A-34, A-56, A-70, A-72, A-91**

### Domed Adjustable Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 326046
- White: 326048

#### Finish/Part No. 155°F (68°C)

- Chrome: 326051
- White: 326053



- cULus Approved:** *GL2845, GL4245, GL5622, GL5646, GL5649, GL5657, GL8104, GL8145, GL8149* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- FOR FULL DESCRIPTION SEE PAGES: A-33, A-35, A-37, A-57, A-73**
- cULus Approved:** *GL2856, GL4256, GL5677, GL5678, GL8173, GL8177* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 155°F (68°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate; 200°F (93°C) Sprinkler with 155°F (68°C) plate
- FOR FULL DESCRIPTION SEE PAGES: A-71, A-92**

### E.C. Domed Adjustable Concealed Sprinklers

#### Finish/Part No. 135°F (57°C)

- Chrome: 329489
- White: 329491

#### Finish/Part No. 155°F (68°C)

- Chrome: 329495
- White: 329497



- cULus Approved:** *GL5613, GL8113* - 135°F (57°C) Sprinkler with 135°F (57°C) plate; 155°F (68°C) Sprinkler with 135°F (57°C) plate; 175° (79°C) Sprinkler with 155°F (68°C) plate
- FOR FULL DESCRIPTION SEE PAGE: A-47**
- cULus Approved:** *GL8114* - 135°F (57°C) Sprinkler with 135°F (57°C) plate
- FOR FULL DESCRIPTION SEE PAGE: A-47a**



4077 AIRPARK DRIVE, STANDISH, MICHIGAN 48658  
989-846-4583 FAX 989-846-9231  
1-800-248-0278 www.globesprinkler.com