



**RECESSED ESCUTCHEONS  
AND COVER PLATES  
TO MEET  
IBC-ASCE/SEI 7 CODES FOR  
SEISMIC AREAS C, D, & E**

**RECESSED ESCUTCHEONS**

**2 PC RECESSED**

1/2" Adjustable

**• Finish/Part No. 1/2" NPT**

Chrome: 326201  
White: 326203-W

**Finish/Part No. 3/4" NPT**

Chrome: 326208  
White: 326210-W

3/4" Adjustable

**• Finish/Part No. 1/2" NPT**

Chrome: 326170  
White: 326172-W

**Finish/Part No. 3/4" NPT**

Chrome: 326177  
White: 326179-W

**1/2" Adjustable Recessed Model Numbers**

• **cULus Approved:** 2810,4110,4210,4230,4231, 4234,4710,5628,5630,5631,8101,8107,8128,8129, 8151 & 8174

• **cULUs & FM Approved:** 5601,8106, 8156 & 5635

**3/4" Adjustable Recessed Model Numbers Seismic**

• **cULus Approved:** 2801,2826,2851,2870,4201,4226, 4231,4251,4270,5601,5602,5626,5628,5635,5636,5641, 5642,5652,5670,5680,5685,5686,8101,8102,8152,8106, 8107,8109,8127,8128,8129,8135,8141,8157,8159,8171, 8174,8179,8185

• **cULus & FM Approved:** 5651, 8156, 8151 & 5679

• **FOR FULL DESCRIPTIONS SEE PAGES: A-24-EQ, A-41-EQ, A-55-EQ, A-67-EQ, A-76-EQ & A-90-EQ**



**OPTIONAL IBC SEISMIC  
RECESSED ESCUTCHEON**

**CONCEALED COVER PLATES**

For "The Inch" Quick Response GL5606&

Standard Response GL5653

**• Finish/Part No. 135°**

Chrome: 332821  
White: 332822

**• Finish/Part No. 155°**

Chrome: 332827  
White: 332828

• **cULus Approved:** GL5653 -135°F (57°C) with plate 135°F (57°C); 155°F (68°C) with plate 135°F (57°C); 155°F (68°C) with plate (68°C); 175°F (79°C) with plate 155°F (68°C); 200°F (93°C) with plate 155°F (68°C)

• **FOR FULL DESCRIPTIONS SEE PAGES: A-38-EQ, & A-69-EQ**



**OPTIONAL  
4 1/2" diameter  
WHITE ADJUSTABLE  
CONCEALED COVER PLATE**